



PURCHASING SECTION
MANUEL B. UTZURRUM BUSINESS & FINANCE CENTER
SILLIMAN UNIVERSITY
Building Competence, Character & Faith

OCTOBER 3, 2017

INVITATION TO SUBMIT PRICE QUOTATION FOR THE FOLLOWING ITEMS:

- 2 units- Data loggers-Onset Comp UX100-011 w/ BFW-PRO-CD,HOBO temp/RH 2.5% data logger w/ HOBOWare Pro CD software and USB cable or equivalent offer
- 1 set - Platform shaker (Labnet Orbit 1000, w/ Labnet S2031-13 spring w/ loaded platform or equivalent offer
- 1 set- Spectrophotometer-Dynamica RB-10-220 w/ 46-03-0012, Ratio beam UV-Vis spectrophotometer with set of 7 pc quartz cuvettes or equivalent offer.....
- 5 units- Stereomicroscope-Optika ST-30-2LED, Binocular, LED lighting or equivalent offer
- 1 unit - Platform-Unico, Platform Rotator, L-RT30C-E, Origin: U.S.A. or equivalent offer
Specs:
Size: 10.4 in x 9.2 in x 6.0 in (263 x 234 x 153 mm)
Shipping size: 12.2 in x11.2 in x 7.4 in (311 x 285 x 187 mm)
Weight: 9.8 lbs (4.4 kg)
Shipping Weight: 10.8 lbs (4.9kg)
- 1 unit - Stereo microscope- Motic stereomicroscope, Binocular Head, Model SMZ-140-N2GG , Origin-Hongkong or equivalent offer.....
- 1 unit- Light Meter (Digital, high end), Standard Portable Lux Meter with waterproof probe,MW700 , Milwaukee brand (Hungary)or equivalent offer
- Specs:
Range- 0.000 to 1999 Lux, 2000 to 19999 Lux, 20000 to 50000Lux;
Range Setting- manual through key buttons;
Resolution - 1 Lux 10Lux, 100 Lux;
Accuracy- $\pm 6\%$ of reading ± 1 digit;
Peak Wave Length- 560nm;
Sensor Type- silicon photodiode;
Sensor Sensitivity- 100 scotopic Lux;
Sensor Stability- $\pm 2\%$ change per year (in the first two years);
Environment- 0 to 50°C / 32 to 122°F; max RH 95%;
Battery Type- 1 x 9V (IEC 6LR61) alkaline;
Battery Life- approximately 150 hours of continuous use;
Auto-off- after about 5 minutes of non-use;
Weight- approximately 270g (meter with sensor)

1 unit- Vortex Mixer, brand-Dlab (USA); MX-S (adjustable speed)
or equivalent offer
Specs:
Voltage- 110-120V/220-230V, 50/60Hz;
Power- 60 W;
Mixing motion- Orbital;
Orbital diameter- 4mm;
Motor type- Shaded pole motor;
Motor rating input- 58W;
Motor rating output- 10W;
Speed range- 0-2500rpm;
Speed display- Scale;
Run type- Touch operation/Continuous;
Dimensions [W x H x D]- 127x130x160mm;
Weight- 3.5kg;
Permissible ambient temperature- 5-40°C;
Permissible relative humidity- 80%;
Protection class- IP21

For further details, please contact Dr. Robert S. Guinoo II, Chairman, Biology Dept.
at (035) 4226002 local 314.

Deadline for Submission of Sealed Bid: October 12, 2017, 8:30 a.m., Purchasing
Section, Business & Finance Office, Silliman University, Dumaguete City

Opening of Sealed Bid: October 12, 2017, 10:00 a.m. at the Office of the Vice
President for Finance & Administration.

Prepared by:

Approved by:


MRS. HERMOSILA E. SALBORO
Purchasing Officer


ATTY. FE MARIE D. DICEN-TAGLE
VP for Finance & Administration